


# OR 90° Shore FPM

Кръгло уплътнение, 90SH FKM (FPM)

## Свойства

|                  |                        |
|------------------|------------------------|
| Конструкция      | кръгло уплътнение      |
| Температура min. | -15 °C                 |
| Температура max. | 200 °C                 |
| Материал         | FPM 90 твърдост по Шор |



|                           |                                      |
|---------------------------|--------------------------------------|
| Bestellnummer / Item code |                                      |
| OR 36.09-3.53 V           |                                      |
| d1 (mm) x 100             | Werkstoff / Material<br>s (mm) x 100 |

## Артикул

| Обозначение        | d1<br>(mm) | d2<br>(mm) | s<br>(mm) |
|--------------------|------------|------------|-----------|
| OR 15.6-1.78 V90   | 15,60      | 19,16      | 1,78      |
| OR 50.39-3.53 V90  | 50,39      | 57,45      | 3,53      |
| OR 91.44-5.34 V90  | 91,44      | 102,12     | 5,34      |
| OR 91.67-3.53 V90  | 91,67      | 98,73      | 3,53      |
| OR 117.07-3.53 V90 | 117,07     | 124,13     | 3,53      |
| OR 266.29-3.53 V90 | 266,29     | 273,35     | 3,53      |