

K-FLAMM SCHLAUCH

Flame tube

HANSA FLEX

Свойства

Диапазон на използване welding equipment
welding robots
welding machines
Welding Related areas

Цвят черен

Температура min. -40 °C

Температура max. 90 °C



Допълнителна информация

- Flame retardant according to UL94 V2/V0
- Welding-spark resistant
- Halogen-free according to EN 50267-2-1 (complies with IEC 60754-1)
- LABS free (free from paint-adhesion inhibiting substances)
- UV-resistant
- can be used with drag chains
- flexible
- resistant to bending
- very good wear resistance
- plasticiser free

Артикул

| Обозначение | Вътрешен Ø (mm) | Външен Ø (mm) | Дебелина на стената (mm) | Радиус на огъване мин. (mm) | Max. working pressure resistance at 23°C (bar) | Дължина на ролката (m) |
|----------------|-----------------|---------------|--------------------------|-----------------------------|--|------------------------|
| K- 07 10 13 27 | 2,0 | 4,0 | 1,0 | 7 | 27 | 50 |
| K- 07 10 13 28 | 4,0 | 6,0 | 1,0 | 8 | 20 | 50 |
| K- 07 10 13 29 | 4,0 | 8,0 | 2,0 | 9 | 23 | 50 |
| K- 07 10 13 30 | 6,0 | 10,0 | 2,0 | 15 | 21 | 50 |
| K- 07 10 13 31 | 8,0 | 12,0 | 2,0 | 26 | 18 | 50 |
| K- 07 10 13 32 | 10,0 | 14,0 | 2,0 | 38 | 13 | 50 |
| K- 07 10 13 33 | 11,0 | 16,0 | 2,5 | 65 | 15 | 50 |