K-DIFFERENZDRUCKMANO Z

Differential pressure gauges with parallel male connector

Свойства

тип	711.12
Изпълнение	Bourdon-tube pressure gauge with parallel male connector and two separate measuring systems
Приложение	to measure differential pressures or two different pressures For gaseous or liquid media which do not corrode copper alloy,do not have high viscosity and do not crystallise
клас качество	1,6
температура на средата	макс. +60 °C
околна температура	-20 °C до +60 °C
корпус, пръстен	Steel, black
материал измервателно звено и механизъм със стрелка	медна сплав
зрително стъкло	Flat instrument glass



Указание

Други данни при запитване.

Артикул

Обозначение	Диапазон на измерване	Ø (mm)	Съединение
K- 07 20 00 55	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 00 56	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 00 57	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 00 58	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 00 59	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 60	0 - 10.0 bar	100,0	G 1/2"

Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.