

# K-MANO

Pressure gauges (CrNi steel type / connection on rear)

**HANSA FLEX**

## Свойства

тип	232.50
Изпълнение	Bourdon-tube pressure gauge, CrNi steel type, all-stainless steel
Приложение	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
клас качество	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
температура на средата	max. +200 °C
околна температура	-40 °C to +60 °C
корпус	CrNi steel
зрително стъкло	Laminated safety glass Ø 63 = Polycarbonate



## Указание

Други данни при запитване.

## Артикул

Обозначение	Диапазон на измерване	Ø (mm)	Съединение
K- 07 20 06 10	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 06 11	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 06 12	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 06 13	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 06 14	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 06 15	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 06 16	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 06 17	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 06 18	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 06 19	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 00 53	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 54	0 - 10.0 bar	100,0	G 1/2"