K-MANO 1

Pressure gauges (CrNi steel type / safety housing)

Свойства

тип	232.30
Изпълнение	Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)
Приложение	For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere
клас качество	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
температура на средата	max. +200 °C
околна температура	-40 °C to +60 °C
корпус	CrNi steel
зрително стъкло	Laminated safety glass Ø 63 = Polycarbonate



Указание

Други данни при запитване.

Описание

Safety version with more fracture-resistant separating wall

Артикул

Обозначение	Диапазон на измерване	Ø (mm)	Съединение
K- 07 20 07 15	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 07 16	0 - 1.6 bar	63,0	G 1/4"
K- 07 20 07 17	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 07 18	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 07 19	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 07 20	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 07 21	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 07 22	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 07 23	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 07 24	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 07 25	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 01 97	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 01 98	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 01 99	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 02 00	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 02 01	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 02 02	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 02 03	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 02 04	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 02 05	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 02 06	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 02 07	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 02 08	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 02 09	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 02 10	0 - 400.0 bar	100,0	G 1/2"

Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.