K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

Свойства

работна температура	-60 °C to +100 °C (PA 12)
Свойства	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Дължина на тръбата	3 m
Опаковъчно звено	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
Материал	Polyamid PA 12, hard (according to DIN 73378)



Указание

Operating pressure with 2.5 x overpressure safety!
Други данни при запитване.

Описание

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Артикул

Обозначение	Външен Ø на тръбата (mm)	вътрешно Ø на тръба (mm)	макс. работно налягане при 20°C (bar)	Цвят
K- 07 10 04 57	12	9	38	син
K- 07 10 04 59	12	9	38	черен
K- 07 10 04 61	15	12	25	син
K- 07 10 04 63	15	12	25	черен
K- 07 10 04 65	18	14	28	син
K- 07 10 04 67	18	14	28	черен
K- 07 10 04 69	22	18	22	син
K- 07 10 04 71	22	18	22	черен
K- 07 10 04 73	28	23	20	син
K- 07 10 04 75	28	23	20	черен

Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.