K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

Свойства

работна температура	-60 °C to +100 °C (PA 12)
Свойства	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Дължина на тръбата	3 m
Опаковъчно звено	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Материал	Polyamid PA 12, hard (according to DIN 73378)



Указание

Operating pressure with 2.5 x overpressure safety!
Други данни при запитване.

Описание

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Артикул

Обозначение	Външен Ø на тръбата (mm)	вътрешно Ø на тръба (mm)	макс. работно налягане при 20°C (bar)	Цвят
K- 07 10 04 56	12	9	38	син
K- 07 10 04 58	12	9	38	черен
K- 07 10 04 60	15	12	25	син
K- 07 10 04 62	15	12	25	черен
K- 07 10 04 64	18	14	28	син
K- 07 10 04 66	18	14	28	черен
K- 07 10 04 68	22	18	22	син
K- 07 10 04 70	22	18	22	черен
K- 07 10 04 72	28	23	20	син
K- 07 10 04 74	28	23	20	черен

Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.