

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Свойства

| | |
|---------------------|--|
| работна температура | -60 °C to +100 °C (PA 12) |
| Свойства | Resistant to corrosion, vibration, impact, ageing, high pressures and heat |
| Дължина на тръбата | 3 m |
| Опаковъчно звено | 20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units! |
| Материал | Polyamid PA 12, hard (according to DIN 73378) |



Указание

Operating pressure with 2.5 x overpressure safety!

Други данни при запитване.

Описание

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Артикул

| Обозначение | Външен Ø на тръбата (mm) | вътрешно Ø на тръба (mm) | макс. работно налягане при 20°C (bar) | Цвят |
|----------------|--------------------------|--------------------------|---------------------------------------|-------|
| K- 07 10 04 56 | 12 | 9 | 38 | син |
| K- 07 10 04 58 | 12 | 9 | 38 | черен |
| K- 07 10 04 60 | 15 | 12 | 25 | син |
| K- 07 10 04 62 | 15 | 12 | 25 | черен |
| K- 07 10 04 64 | 18 | 14 | 28 | син |
| K- 07 10 04 66 | 18 | 14 | 28 | черен |
| K- 07 10 04 68 | 22 | 18 | 22 | син |
| K- 07 10 04 70 | 22 | 18 | 22 | черен |
| K- 07 10 04 72 | 28 | 23 | 20 | син |
| K- 07 10 04 74 | 28 | 23 | 20 | черен |