

# K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

**HANSA FLEX**

## Свойства

работна температура	-60 °C to +100 °C (PA 12)
Свойства	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Дължина на тръбата	3 m
Опаковъчно звено	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Материал	Polyamid PA 12, hard (according to DIN 73378)



## Указание

Operating pressure with 2.5 x overpressure safety!

Други данни при запитване.

## Описание

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Артикул

Обозначение	Външен Ø на тръбата (mm)	вътрешно Ø на тръба (mm)	макс. работно налягане при 20°C (bar)	Цвят
K- 07 10 04 56	12	9	38	син
K- 07 10 04 58	12	9	38	черен
K- 07 10 04 60	15	12	25	син
K- 07 10 04 62	15	12	25	черен
K- 07 10 04 64	18	14	28	син
K- 07 10 04 66	18	14	28	черен
K- 07 10 04 68	22	18	22	син
K- 07 10 04 70	22	18	22	черен
K- 07 10 04 72	28	23	20	син
K- 07 10 04 74	28	23	20	черен