K-SPIR SCHL B DREH VERSCHRAU

Spiral hose, with swivel adapter fitted at both ends and kink protector

Свойства

Приложение	Air, gases, oils, greases, fuels, organic and inorganic substances
работна температура	-40 °C to +100 °C
вид съединение	connection nipples and coupling NW 7,2



Указание

Други данни при запитване.

Описание

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Артикул

Обозначение	Ø маркуч отвътре (mm)	Ø маркуч отвън (mm)	Резба	Ø спирала отвън (mm)	навивки	Max. working pressure resistance at 23°C (bar)	макс. работна дължина (m)
K- 07 10 07 34	3,1	4,7	R 1/8	38	36	22	2,5
K- 07 10 07 35	3,1	4,7	R 1/8	38	72	22	5,0
K- 07 10 07 36	3,1	4,7	R 1/8	38	108	22	7,5
K- 07 10 07 37	4,8	6,3	R 1/4	75	15	16	2,5
K- 07 10 07 38	4,8	6,3	R 1/4	75	30	16	5,0
K- 07 10 07 39	4,8	6,3	R 1/4	75	45	16	7,5
K- 07 10 07 40	6,3	7,9	R 1/4	75	15	13	2,5
K- 07 10 07 41	6,3	7,9	R 1/4	75	30	13	5,0
K- 07 10 07 42	6,3	7,9	R 1/4	75	45	13	7,5
K- 07 10 07 28	7,9	9,5	R 1/4	115	10	12	2,5
K- 07 10 07 29	7,9	9,5	R 1/4	115	20	12	5,0
K- 07 10 07 30	7,9	9,5	R 1/4	115	30	12	7,5
K- 07 10 07 31	9,5	11,8	R 3/8	140	8	11	2,5
K- 07 10 07 32	9,5	11,8	R 3/8	140	15	11	5,0
K- 07 10 07 33	9,5	11,8	R 3/8	140	23	11	7,5

Принадлежности

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.