

K-SPIR SCHL

Spiral hose, without fittings

Свойства

Приложение	Air, gases, oils, greases, fuels, organic and inorganic substances
работна температура	-40 °C to +100 °C



Указание

Други данни при запитване.

Описание

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Артикул

Обозначение	Ø маркуч отвътре (mm)	Ø маркуч отвън (mm)	Ø спирала отвън (mm)	навивки	Max. working pressure resistance at 23°C (bar)	макс. работна дължина (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

Принадлежности

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector