K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

Свойства

вид съединение	with kink protector, swivel type
работна температура	-40 °C to +74 °C



Указание

Други данни при запитване.

Описание

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Артикул

Обозначение	Резба	Ø маркуч отвътре (mm)	Ø маркуч отвън (mm)	Ø външна навивка (mm)	Max. working pressure resistance at 23°C (bar)	макс. работна дължина (m)
K- 07 10 07 43	G 1/4	6,3	9,5	42	14	3,0
K- 07 10 07 44	G 1/4	6,3	9,5	42	14	6,0
K- 07 10 07 45	G 1/4	6,3	9,5	42	14	7,5
K- 07 10 07 46	G 3/8	8,0	12,0	55	14	3,0
K- 07 10 07 47	G 3/8	8,0	12,0	55	14	6,0
K- 07 10 07 48	G 3/8	8,0	12,0	55	14	7,5

Принадлежности

K-DREHBARE VERSCHRAUBUNG	Swivel adapters

Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.