

K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

HANSA FLEX

Свойства

вид съединение with kink protector, swivel type

работна температура -40 °C to +74 °C



Указание

Други данни при запитване.

Описание

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Артикул

| Обозначение | Резба | Ø маркуч отвътре (mm) | Ø маркуч отвън (mm) | Ø външна навивка (mm) | Max. working pressure resistance at 23°C (bar) | макс. работна дължина (m) |
|----------------|-------|-----------------------|---------------------|-----------------------|--|---------------------------|
| K- 07 10 07 43 | G 1/4 | 6,3 | 9,5 | 42 | 14 | 3,0 |
| K- 07 10 07 44 | G 1/4 | 6,3 | 9,5 | 42 | 14 | 6,0 |
| K- 07 10 07 45 | G 1/4 | 6,3 | 9,5 | 42 | 14 | 7,5 |
| K- 07 10 07 46 | G 3/8 | 8,0 | 12,0 | 55 | 14 | 3,0 |
| K- 07 10 07 47 | G 3/8 | 8,0 | 12,0 | 55 | 14 | 6,0 |
| K- 07 10 07 48 | G 3/8 | 8,0 | 12,0 | 55 | 14 | 7,5 |

Принадлежности

K-DREHBARE VERSCHRAUBUNG Swivel adapters