


K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

HANSA FLEX

Свойства

Работно налягане	See table. All values referred to a medium temperature of 50 °C (static working pressure)
протичане въздух	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
температура на средата	-20 °C to +90 °C
корпус, втулка	POM (Delrin), white
клапан	Stainless steel 1.4305
пружина, пружинен спирален пръстен, сачми	stain less steel
уплътняващ материал	NBR



Указание

Други данни при запитване.

Описание

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Артикул

Обозначение	Съединение	Работно налягане (bar)	Дължина (mm)	NW	SW (mm)
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36