


K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Свойства

Работно налягане	0 - 35 bar, maximum static working pressure (non-pulsating)
протичане въздух	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
температура на средата	-20 °C to +100 °C
деблокираща втулка	Anodised aluminium
пружина, пружинен спирален пръстен, сачми	stain less steel
уплътняващ материал	NBR



Указание

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Други данни при запитване.

Описание

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Артикул

Обозначение	Съединение	Цвят	Дължина (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	зелен	45,0	14
K- 07 35 06 81	G 1/4 male	зелен	47,0	17
K- 07 35 06 82	G 1/8 female	зелен	45,0	14
K- 07 35 06 83	G 1/4 female	зелен	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	син	45,0	14
K- 07 35 06 89	G 1/4 male	син	47,0	17
K- 07 35 06 90	G 1/8 female	син	45,0	14
K- 07 35 06 91	G 1/4 female	син	47,0	17
K- 07 35 06 92	G 1/8 male	червен	45,0	14
K- 07 35 06 93	G 1/4 male	червен	47,0	17
K- 07 35 06 94	G 1/8 female	червен	45,0	14
K- 07 35 06 95	G 1/4 female	червен	47,0	17