


K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

HANSA FLEX

Свойства

Работно налягане	0 - 35 bar, maximum static working pressure (non-pulsating)
протичане въздух	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
температура на средата	-20 °C to +100 °C
корпус	Brass
клапан	Die-cast zinc, nickel-plated
деблокираща втулка	Anodised aluminium
пружина, пружинен спирален пръстен, сачми	stain less steel
уплътняващ материал	NBR



Указание

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Други данни при запитване.

Описание

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Артикул

Обозначение	Съединение	Цвят	Дължина (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	зелен	57,5	19
K- 07 35 08 02	G 3/8 male	зелен	57,5	19
K- 07 35 08 03	G 1/4 female	зелен	55,5	19
K- 07 35 08 04	G 3/8 female	зелен	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	син	57,5	19
K- 07 35 08 10	G 3/8 male	син	57,5	19
K- 07 35 08 11	G 1/4 female	син	55,5	19
K- 07 35 08 12	G 3/8 female	син	54,5	19
K- 07 35 08 13	G 1/4 male	червен	57,5	19
K- 07 35 08 14	G 3/8 male	червен	57,5	19
K- 07 35 08 15	G 1/4 female	червен	55,5	19
K- 07 35 08 16	G 3/8 female	червен	54,5	19