

# K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

**HANSA FLEX**

## Свойства

|   |   |
|---|---|
| Работно налягане                          | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| протичане въздух                          | 1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)             |
| температура на средата                    | -20 °C to +100 °C   |
| корпус                                    | Brass   |
| клапан                                    | Die-cast zinc, nickel-plated                                |
| деблокираща втулка                        | Anodised aluminium  |
| пружина, пружинен спирален пръстен, сачми | stain less steel  |
| уплътняващ материал                       | NBR   |



## Указание

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Други данни при запитване.

## Описание

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

## Артикул

| Обозначение    | Съединение   | Цвят   | Дължина (mm) | SW (mm) |
|----------------|--------------|--------|--------------|---------|
| K- 07 35 08 01 | G 1/4 male   | зелен  | 57,5         | 19      |
| K- 07 35 08 02 | G 3/8 male   | зелен  | 57,5         | 19      |
| K- 07 35 08 03 | G 1/4 female | зелен  | 55,5         | 19      |
| K- 07 35 08 04 | G 3/8 female | зелен  | 54,5         | 19      |
| K- 07 35 08 05 | G 1/4 male   | Brown  | 57,5         | 19      |
| K- 07 35 08 06 | G 3/8 male   | Brown  | 57,5         | 19      |
| K- 07 35 08 07 | G 1/4 female | Brown  | 55,5         | 19      |
| K- 07 35 08 08 | G 3/8 female | Brown  | 54,5         | 19      |
| K- 07 35 08 09 | G 1/4 male   | син    | 57,5         | 19      |
| K- 07 35 08 10 | G 3/8 male   | син    | 57,5         | 19      |
| K- 07 35 08 11 | G 1/4 female | син    | 55,5         | 19      |
| K- 07 35 08 12 | G 3/8 female | син    | 54,5         | 19      |
| K- 07 35 08 13 | G 1/4 male   | червен | 57,5         | 19      |
| K- 07 35 08 14 | G 3/8 male   | червен | 57,5         | 19      |
| K- 07 35 08 15 | G 1/4 female | червен | 55,5         | 19      |
| K- 07 35 08 16 | G 3/8 female | червен | 54,5         | 19      |