

K-GRUNDEJEKTION SBP-C

Basic ejectors »SBP-C« with blow-off valve, with integrated silencer

HANSA**FLEX**

Свойства

Свойства	Vacuum generator with a single nozzle, available in six power ratings, with a high maximum vacuum value (85%) Connection of compressed air and vacuum with push-in coupling Basic housing with connection facility for a vacuum switch Maximum suction capacity with minimum compressed air consumption Minimum size, low weight Various power ratings for optimised air consumption
-----------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


Приложение	For universal use in handling systems with very high dynamic movements Handling all kinds of air-tight components For use in separation systems where space is restricted. InConstruction of ejector blocks for centralised or decentralised individual control of suction pads.
-------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

система от дюзи	Brass
------------------------	-------

Съединение	Push-in coupling
-------------------	------------------

шумозаглушител	Plastic
-----------------------	---------

основен корпус	Impact-resistant plastic
-----------------------	--------------------------



Указание

Други данни при запитване.

Описание

Purely pneumatic vacuum ejector that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

Артикул

Обозначение	размер на дюза	засмукващ клапан положение на покой	извод за въздух под налягане	вакуумно съединение	Размер
K-07 45 01 19	1,0	NO	6 mm	8 mm	142mm x 15mm x 50mm
K-07 45 01 21	1,5	NO	6 mm	8 mm	142mm x 15mm x 50mm
K-07 45 01 23	2,0	NO	8 mm	10 mm	228mm x 20mm x 72mm
K-07 45 01 25	2,5	NO	8 mm	10 mm	228mm x 20mm x 72mm

Принадлежности

K-ERSATZSCHALDAEMPFER 1	Replacement silencers
K-GRUNDPLATTEN 1	Base plate
K-BEFESTIGUNGSSAETZE 1	Mounting kit