

K-INLINE-EJEKTOREN VR

Inline ejectors »VR«, screw connection

HANSA FLEX

Свойства

Свойства Vacuum generator with high maximum vacuum level (85% vacuum)
No moving parts, which means no wear and no maintenance
ultra small footprint, suitable for confined spaces
minimal air consumption
\nlow noise

Приложение by screwing / plugging into the distribution beam
direct attachment to the suction pad
for handling various workpieces

корпус Aluminium eloxed (type VR)

система от дюзи Brass (type VR)

Съединение щекерно съединение



Указание

Други данни при запитване.

Описание

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Артикул

Обозначение	размер на дюза	съединение отработен въздух	извод за въздух под налягане	вакуумно съединение	степен на евакуиране	разход на въздух засмукване (L/min)	макс. капацитет на засмукване (L/min)	Дължина (mm)	Работно налягане (bar)
K- 07 45 01 29	0,7	M 5 male	G 1/4 IG	G1/8 female	90 %	21,0	14,0	35,0	5,0
K- 07 45 01 30	0,9	M 5 male	G 1/4 IG	G1/8 female	89 %	36,0	21,0	35,0	5,0