


K-INLINE-EJEKTOREN SLP

Inline ejectors »SLP«, plug connection

HANSA FLEX

Свойства

Свойства	Vacuum generator with high maximum vacuum level (85% vacuum) No moving parts, which means no wear and no maintenance ultra small footprint, suitable for confined spaces minimal air consumption \nlow noise
Приложение	by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces
корпус	plastic (Typ SLP)
система от дюзи	Brass (type VR)
Съединение	thread connector



Указание

Други данни при запитване.

Описание

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Артикул

Обозначение	размер на дюза	съединение отработен въздух	извод за въздух под налягане	вакуумно съединение	степен на евакуиране	разход на въздух засмукване (L/min)	макс. капацитет на засмукване (L/min)	Дължина (mm)	Работно налягане (bar)
K- 07 45 01 27	0,5	-	4 mm	4 mm	85 %	13,0	8,0	57,0	4,5
K- 07 45 01 28	0,7	-	4 mm	4 mm	85 %	25,0	16,0	57,0	4,5