

K-FEDERSTOESSEL

Spring plungers

HANSA FLEX

Свойства

Приложение	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Температура min.	0 °C
Температура max.	80 °C
свързване на смукател	M 3 female
Изпълнение	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
ход на пружина	5,0 mm



Указание

Други данни при запитване.

Описание

Suitable for all round or oval suction pads in our standard range.

Артикул

Обозначение	вакуумно съединение	Дължина (mm)	вертикално натоварване (N/m ²)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400