

# K-FEDERSTOESSEL

Spring plungers

**HANSA FLEX**

## Свойства

Приложение	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Температура min.	0 °C
Температура max.	80 °C
свързване на смукател	M 3 female
Изпълнение	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
ход на пружина	5,0 mm



## Указание

Други данни при запитване.

## Описание

Suitable for all round or oval suction pads in our standard range.

## Артикул

Обозначение	вакуумно съединение	Дължина (mm)	вертикално натоварване (N/m <sup>2</sup> )
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400