

# K-VAKUUMSENSOR DIGITAL

Vacuum sensor, digital

**HANSA FLEX**

## Свойства

|                              |   |
|------------------------------|---|
| <b>Приложение</b>            | Measurement of vacuum values close to the suction pad<br>Remote evaluation of the signals<br>Processing the output signals, for example, by PLC |
| <b>Течности</b>              | dry, oil-free air and non-aggressive gases  |
| <b>Температурен диапазон</b> | 0 - 50 °C   |
| <b>изходящ сигнал</b>        | 1 to 5 analogous to V   |
| <b>хистерезис</b>            | Fixed: 20 mbar (model with digital sensor)  |
| <b>дължина кабел</b>         | 3 m   |
| <b>вид защита</b>            | IP 40   |



## Указание

Други данни при запитване.

## Описание

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy.

## Артикул

| Обозначение    | Съединение | H<br>(mm) | L<br>(mm) | Диапазон на измерване | Напрежение   |
|----------------|------------|-----------|-----------|-----------------------|--------------|
| K- 07 45 01 57 | M 5 male   | 16,9      | 21,0      | -1 bis 0 bar          | 10 - 24 V DC |