

# K-DRS MDR 5 O ENTLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

**HANSA FLEX**

## Свойства

|                              |                                    |
|------------------------------|------------------------------------|
| температура на средата       | -5 °C to +80 °C                    |
| макс. налягане на изключване | 16 bar                             |
| капацитет на включване       | 5,5 kW                             |
| вид контакт                  | NC (3-pole)                        |
| макс. честота на включване   | 120 (electrical), 600 (mechanical) |
| вид защита                   | IP 54                              |



## Указание

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Други данни при запитване.

## Описание

Three-phase version

## Указания за поръчка

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Допълнителна информация

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

## Артикул

| Обозначение    | извод за въздух под налягане | диапазон за настройка |
|----------------|------------------------------|-----------------------|
| K- 07 30 24 24 | G 1/2                        | 2,0 - 11,0 bar        |
| K- 07 30 24 26 | G 1/2                        | 2,5 - 16,0 bar        |