# K-BKR STAN DOP VA


Stainless steel ball valves, double-acting actuator

HANSA FLEX

## Свойства

| | |
|---|---|
| **Конструкция** | Pneumatic actuators, in double- or single acting version, with integrated end-position feedback |
| **Работно налягане** | max. 63 bar (depending on temperature and nominal size) |
| **работна температура** | -20 °C to +70°C |
| **ъгъл на завъртане** | 90 ° |
| **стандартни места на срез** | Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S |
| **налягане на управление** | 5.5 bar |
| **клапанен адаптер** | Acc. to NAMUR |
| **задвижване** | aluminium eloxed |
| **уплътнение на задвижване** | NBR |
| **сферичен кран** | Stainless steel 1.4401,with ISO-flange plate |
| **уплътнение сферичен кран** | PTFE |






## Указание

Други данни при запитване.

## Описание

2-way cock, 3-piece, full bore

## Артикул

| Обозначение | DN | Резба | A (mm) | B (mm) | D (mm) | L (mm) | SW (mm) |
|---|---|---|---|---|---|---|---|
| **K- 07 30 02 42** | 15 | Rp 1/2 | 133,0 | 144,0 | 24,0 | 75,0 | 29 |
| **K- 07 30 02 43** | 15 | Rp 1/2 | 116,0 | 135,0 | 24,0 | 75,0 | 29 |
| **K- 07 30 02 44** | 20 | Rp 3/4 | 133,0 | 148,0 | 27,0 | 80,0 | 35 |
| **K- 07 30 02 45** | 20 | Rp 3/4 | 116,0 | 139,0 | 27,0 | 80,0 | 35 |
| **K- 07 30 02 46** | 25 | Rp 1 | 133,0 | 157,0 | 30,0 | 90,0 | 41 |
| **K- 07 30 02 47** | 32 | Rp 1 1/4 | 137,0 | 176,0 | 37,0 | 110,0 | 50 |
| **K- 07 30 02 48** | 40 | Rp 1 1/2 | 137,0 | 186,0 | 40,0 | 120,0 | 58 |
| **K- 07 30 02 49** | 50 | Rp 2 | 161,0 | 207,0 | 50,0 | 140,0 | 74 |
| **K- 07 30 02 50** | 65 | Rp 2 1/2 | 180,0 | 238,0 | 60,0 | 185,0 | 89 |
| **K- 07 30 02 51** | 80 | Rp 3 | 209,0 | 257,0 | 82,0 | 205,0 | 104 |

*Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.*