
K-MV G 230 V, 50 - 60 HZ IV

Normally closed, 230 V / 50 to 60 Hz, internal pilot control



| Свойства | | | |
|---|--|--|--|
| електрическо съединение | ISO 4400 (Pg 11P connector socket) | | |
| вид защита | IP65 (with connector socket fitted) | | |
| температура на средата | max. +90 °C | | |
| Работно налягане | min. 0,35 bar; max. 8,5 bar | | |
| съединение за обезвъздушаване при модификация 2 | G 3/8 (K-07302231 und K-07302304), G 3/4 (K-07302232 und K-07302305, \nK-07302233 und K-07302306), Silencers can be retrofitte | | |
| корпус | Aluminium | | |
| вътрешни части | Stainless steel | | |
| мембрана | Type 1 TPE (Hydrel); Type 2 CR (chlorophene/neoprene) | | |
| уплътнение | Perbunan (NBR) | | |





Указание

Други данни при запитване.

Описание

Environmental protection today demands state-of-the-art cleaning processes. Dust filter systems are an indispensable aid to pollution control. The fabric filters installed in these systems are cleaned by blowing in compressed air pulses in quick succession counter to the main direction of flow. The solenoid valves used for this purpose are characterised by the following application-specific design features:

Angle type of construction to optimise the air flow

Full cross-section at the valve seat

Extremely fast opening and closing

Can be retrofitted in sizes 1 1/2- to 2 1/2)

Easy maintenance and repair because diaphragm and wearing parts are instantly available

Extremely fast opening and closing

The valves are not suitable as shut-off devices for standard applications.

| Артикул | | | | | | |
|----------------|---------|------|-----------|-----------|-------------|--|
| Обозначение | Резба | NW | A (mm) | B (mm) | модификация | |
| K- 07 30 22 29 | G 3/4 | 25,0 | 75,0 | 89,0 | 1 | |
| K- 07 30 22 30 | G 1 | 25,0 | 75,0 | 89,0 | 1 | |
| K- 07 30 22 31 | G 1 1/2 | 52,0 | 80,0 | 130,0 | 2 | |
| K- 07 30 22 32 | G 2 | 66,0 | 80,0 | 168,0 | 2 | |
| K- 07 30 22 33 | G 2 1/2 | 66,0 | 80,0 | 168,0 | 2 | |