


Свойства			
диференциално налягане	0 - 16 bar		
температура на средата	-10 °C to +180 °C		
управляващо съединение за въздух	G 1/8		
температура управляваща среда	max. +60 °C		
околна температура	-20 °C to +70 °C		
допустимо статично налягане	Max. 16 bar		
корпус на клапан	Bronze		
свързващ елемент	Stainless steel		
управляваща глава	Polyamide (glass fibre-reinforced)		
бутало	Nickel-plated brass (DN 15 to DN 32), PBT + GF 30% (DN 40 to DN 50)		
шпиндел	Stainless steel		
уплътняващ материал	PTFE		





Указание

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off. Други данни при запитване.

Описание

Angle-seat valves with external pilot control and a self-aligning valve discfor neutral (bronze body) or corrosive (stainless steel body) media. Very high flow due to angled seat design, Water hammer prevented by fluid entry under the disc, Suitable for vacuum operation (low vacuum), NAMUR interface on the piston actuator. 3/2 and 5/2-way valves can be mounted directly.

Допълнителна информация

Other versions e.g. for steam on request

Information on max. operating differential pressures apply for air, gas, corrosive aggressive media, water

Артикул

Обозначение	Α	С	F	Резба	макс. разлика работно налягане	мин. налягане на управление	макс. налягане на управление
	(mm)	(mm)	(mm)		(bar)		
K- 07 30 25 24	163,0	153,0	65,0	G 1/2	16	4	10
K- 07 30 25 25	173,0	163,0	75,0	G 3/4	10	4	10
K- 07 30 25 26	191,0	181,0	75,0	G 3/4	16	4	10
K- 07 30 25 27	206,0	196,0	90,0	G 1	11	4	10
K- 07 30 25 28	246,0	236,0	90,0	G 1	16	4	8
K- 07 30 25 29	255,0	245,0	110,0	G 1 1/4	14	4	8
K- 07 30 25 30	270,0	264,0	120,0	G 1 1/2	11	4	8
K- 07 30 25 31	306,0	300,0	120,0	G 1 1/2	16	4	8
K- 07 30 25 32	316,0	311,0	150,0	G 2	10	4	8