


K-ANSCHLUSSNIP FLACHSAUG IG

Connection nipples for flat suction pads

HANSA FLEX

Свойства

за диаметър на засмукване 20 mm



Указание

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy.

Допълнителна информация

Socket connectors suitable for vacuum («click-clock» series) see page All PA/PE/PU hoses up to size 12 x 9 mm are suitable for vacuum. See page

Артикул

| Обозначение | Резба | Дължина (mm) | NW |
|----------------|--------------|-----------------|-----|
| K- 07 45 00 22 | M 5 female | 10,0 | 2,0 |
| K- 07 45 00 23 | G 1/4 female | 23,0 | 5,5 |
| K- 07 45 00 24 | G 1/8 female | 16,0 | 2,0 |
| K- 07 45 00 25 | G 1/8 female | 16,0 | 2,0 |
| K- 07 45 00 26 | G 1/8 female | 16,0 | 2,0 |
| K- 07 45 00 27 | G 1/8 female | 16,0 | 3,5 |
| K- 07 45 00 28 | G 1/8 female | 16,0 | 3,5 |

е принадлежност към следните продукти

| | |
|----------------------------|---|
| K-FLACHSAUGER RUND NBR | Flat suction pads, round, material NBR |
| K-FLACHSAUGER RUND SILIKON | Flat suction pads, round, material silicone |