
## K-INLINE-DRG AG IG M SEKUNDAERENTLU

Inline pressure regulators, female/male thread, self-relieving



Свойства	
Работно налягане	Max. 25 bar
Температурен диапазон	0 °C to +80 °C
корпус	Aluminium
останалите части	Stainless steel, nitrile rubber, brass





## Указание

Други данни при запитване.

## Описание

Артикул					
Резба	работно налягане предварително настроено	протичане	A (mm)	SW (mm)	
G 1/4	2 bar	600 - 800 l/min	66,6	16	
G 1/4	3 bar	600 - 800 I/min	66,6	16	
G 1/4	4 bar	600 - 800 l/min	66,6	16	
G 1/4	5 bar	600 - 800 l/min	66,6	16	
G 1/4	6 bar	600 - 800 l/min	66,6	16	
G 1/4	8 bar	600 - 800 l/min	66,6	16	
	G 1/4 G 1/4 G 1/4 G 1/4 G 1/4	G 1/4 2 bar G 1/4 3 bar G 1/4 4 bar G 1/4 5 bar G 1/4 6 bar	G 1/4 2 bar 600 - 800 l/min G 1/4 3 bar 600 - 800 l/min G 1/4 4 bar 600 - 800 l/min G 1/4 5 bar 600 - 800 l/min G 1/4 6 bar 600 - 800 l/min	G 1/4     2 bar     600 - 800 l/min     66,6       G 1/4     3 bar     600 - 800 l/min     66,6       G 1/4     4 bar     600 - 800 l/min     66,6       G 1/4     5 bar     600 - 800 l/min     66,6       G 1/4     6 bar     600 - 800 l/min     66,6	