


K-VERSCHLUSSKAPPEN MS

Hexagonal caps - brass

HANSA FLEX

Свойства

| | |
|------------------------|-------------|
| работно налягане | 10 bar |
| температура на средата | max. +90 °C |
| околна температура | Max. +90 °C |



Указание

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.
Други данни при запитване.

Допълнителна информация

Further types and dimensions on request.

Артикул

| Обозначение | Резба | L1 (mm) | SW |
|----------------|---------|------------|-------|
| K- 07 40 10 06 | G 1/8 | 10,0 | 13 mm |
| K- 07 40 10 07 | G 1/4 | 10,0 | 16 mm |
| K- 07 40 10 08 | G 3/8 | 10,0 | 19 mm |
| K- 07 40 10 09 | G 1/2 | 12,0 | 23 mm |
| K- 07 40 10 10 | G 3/4 | 14,0 | 29 mm |
| K- 07 40 10 11 | G 1 | 15,0 | 36 mm |
| K- 07 40 10 12 | G 1 1/4 | 17,0 | 46 mm |
| K- 07 40 10 13 | G 1 1/2 | 19,5 | 53 mm |
| K- 07 40 10 14 | G 2 | 19,5 | 64 mm |