
K-PROP VENTIL LU GA 24 V DC

Proportional valves for controlling the flow of air / gas, 24 VDC, closed when de-energised



Свойства			
Температурен диапазон	Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)		
Течности	Air, neutral gases, water, oil		
диапазон на налягане	Vacuum (max. 8 bar)		
задействане	Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA		
поведение Failsafe	Tight closure in case of loss of voltage		
корпус, гнездо на клапан	Brass		
вътрешни части	Stainless steel		
клапанна тарелка	FKM		
уплътняващ материал	FKM		





Указание

Други данни при запитване.

Описание

Допълнителна информация

We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 $^{\circ}$

Артикул								
Обозначение	Съединение	DN	макс. разлика работно налягане (bar)	A (mm)	В	C (mm)		
K- 07 25 09 91	G 1/4	2	8	85,0	40,0 mm	95,0		
K- 07 25 09 92	G 1/4	3	4	85,0	40,0 mm	95,0		
K- 07 25 09 93	G 3/8	6	1	85,0	48,0 mm	97,0		
K- 07 25 09 94	G 3/8	7	1	85,0	48,0 mm	97,0		

13.11.2025 HANSA-FLEX AG www.hansa-flex.com