K-CHOPPERVERSTAERKER

Chopper amplifier (cabinet mounting)



Свойства	
номинално напрежение	24 V DC
Температурен диапазон	-10 °C to +75 °C (plug amplifier), -10 °C to +60 °C (chopper amplifier)
корпус	PA



Указание

Други данни при запитване.

Описание

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital. <a href="https://document.org/reportional-valves-allow-the-medium-to-be-varied-as-a-function-of-an-electronic-input variable-sh-by-linking-these valves to the electronics, it is possible to improve their accuracy and broaden their range of applications. A pressure regulator, for instance, needs to be suitable for several pressure ranges without having to adjust the pressure manually. <a href="https://doi.org/reportional-valves-control-the-output pressure-in-a-closed-control-loop-proportional-input-valves-control-the-output pressure-in-a-closed-control-loop-proportionally to the selected setpoint signal. This output pressure, in other words, is continually compared with the specified setpoint and automatically adjusted according to actual parameter values.

Α	n	Т	и	K١	71	٦
•	Μ.	•	•	•	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	۰

Обозначение	за уреди със съединение	
K- 07 25 18 03	-	