

# K-WTEH 2-TLG PC-BEHAEL MANO STAN-MI

Service units, 2-piece with polycarbonate bowl and pressure gauge

**HANSA FLEX**

## Свойства

|                                          |                                                                                              |
|------------------------------------------|----------------------------------------------------------------------------------------------|
| входящо налягане                         | Max. 16 bar (polycarbonate bowl),<br>Max. 25 bar (metal bowl)                                |
| температура на средата                   | max. 60 °C                                                                                   |
| околна температура                       | Max. 60 °C                                                                                   |
| протичане                                | 350 l/min (2-piece), 300 l/min (3-<br>piece)                                                 |
| ширина на порите във филтриращия елемент | 5 µm                                                                                         |
| уплътняващ материал                      | NBR                                                                                          |
| корпус                                   | Die-cast zinc, painted silver                                                                |
| наставка прокапване                      | PA (polycarbonate bowl), Zinc-glass-<br>NBR (metal bowl)                                     |
| Drain valve                              | Semi-automatic for variant with<br>polycarbonate bowl, Manual for<br>variant with metal bowl |
| измерване на стойността на протичане     | At P1 = 8 bar, P2 = 6 bar and<br>pressure drop $\Delta p = 1$ bar                            |



## Указание

Други данни при запитване.

## Описание

Compact, two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Артикул

| Обозначение    | Резба | диапазон на регулиране | A<br>(mm) | B        | C<br>(mm) | D<br>(mm) | DN |
|----------------|-------|------------------------|-----------|----------|-----------|-----------|----|
| K- 07 25 14 89 | G 1/8 | 0.5 - 10 bar           | 85,0      | 167,0 mm | 65,0      | 102,0     | 5  |
| K- 07 25 14 91 | G 1/4 | 0.5 - 10 bar           | 85,0      | 167,0 mm | 65,0      | 102,0     | 5  |

## Резервни части

|                                |                                                           |
|--------------------------------|-----------------------------------------------------------|
| K-HALTERBAUSATZ                | Holder                                                    |
| K-SCHALTAFELMUTTER             | Nut                                                       |
| K-ERSATZBEHAELTER MULTI MINI   | Spare tank »multifix-mini« & »standard-mini«              |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter                                 |
| K-VERSCHLEI-SATZ               | Set of wearing parts                                      |
| K-FILTERELEMENT                | Filter element                                            |
| K-AUTOMAT ABLASSVENTIL         | Automatic drain valve                                     |
| K-TROPFAUFSATZ POLYCARBO       | Drip attachment polycarbonate                             |
| K-TROPFAUFSATZ METALL          | Drip attachment metal                                     |
| K-LOESBARE DOPPELNIPPEL MS     | Double nipples                                            |
| K-XV AGM MS NI                 | Double nipples, parallel male thread, nickel-plated brass |