

K-WV 5/2 DIFFERENZIALKOLBEN

5/2-way pilot valves, with differential piston

HANSA FLEX

Свойства

| | |
|------------------------|--|
| Работно налягане | 2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\nvacuum up to 10 bar (external pilot air) |
| мин. работно налягане | 2.5 bar (monostable), 1.0 bar (bistable) |
| Температурен диапазон | -10 °C to +60 °C |
| протичане 6bar и 10bar | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2) |
| протичане 6bar и 5bar | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2) |



Указание

Други данни при запитване.

Артикул

| Обозначение | Съединение | Напрежение | DN | функция | електрическа схема номер | Управление |
|----------------|------------|--------------|----|---------|--------------------------|------------|
| K- 07 15 02 05 | G 1/8 | 24 V DC | 5 | 5/2-way | 36 | |
| K- 07 15 02 06 | G 1/4 | 24 V DC | 8 | 5/2-way | 36 | |
| K- 07 15 25 85 | G 3/8 | 24 V DC | 13 | 5/2-way | 36 | |
| K- 07 15 02 07 | G 1/2" | 24 V DC | 15 | 5/2-way | 36 | |
| K- 07 15 02 08 | G 1/8 | 230 V, 50 Hz | 5 | 5/2-way | 36 | |
| K- 07 15 02 09 | G 1/4 | 230 V, 50 Hz | 8 | 5/2-way | 36 | |
| K- 07 15 25 86 | G 3/8 | 230 V, 50 Hz | 13 | 5/2-way | 36 | |
| K- 07 15 02 10 | G 1/2" | 230 V, 50 Hz | 15 | 5/2-way | 36 | |