

K-BKR KL SERIE 375

Ball valves, 375 series

HANSA**FLEX**

Свойства


Работно налягане max. 70 bar (depending on temperature and nominal size)

ориентировъчни стойности
G 1/4 to G 1: 20 °C: 70 bar, 60 °C: 65 bar,
100 °C: 45 bar, 150 °C: 7 bar, 180 °C: 4 bar,
200 °C: 0 bar
G 1 1/4 to G 1 1/2: 20 °C: 70 bar, 60 °C: 55
bar, 100 °C: 35 bar, 150 °C: 7 bar, 180 °C: 4
bar, 200 °C: 0 bar
G 2: 20 °C: 60 bar, 60 °C: 40 bar, 10

работна температура 200 °C at 0 bar

упътнение 15 % RPTFE (glass fibre reinforced PTFE)

ръчен лост Stainless steel 1.4301



Указание

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Други данни при запитване.

Указания за поръчка

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Допълнителна информация

G thread acc. DIN EN ISO 228-1

Артикул

Обозначение	DN	Резба	A (мм)	B (мм)	L (мм)	Материал
K-07 30 15 36	5	G 1/4	69,0	34,0	39,0	Stainless steel 1.4401/1.4408
K-07 30 15 37	7	G 3/8	83,0	38,0	44,0	Stainless steel 1.4401/1.4408
K-07 30 15 38	10	G 1/2	96,0	41,0	59,0	Stainless steel 1.4401/1.4408
K-07 30 15 39	13	G 3/4	96,0	45,0	60,0	Stainless steel 1.4401/1.4408
K-07 30 29 80	16	G 1	116,0	52,0	72,0	Stainless steel 1.4401/1.4408
K-07 30 29 81	20	G 1 1/4	116,0	57,0	77,0	Stainless steel 1.4401/1.4408
K-07 30 29 82	25	G 1 1/2	158,0	62,0	84,0	Stainless steel 1.4401/1.4408
K-07 30 29 83	32	G 2	158,0	68,0	100,0	Stainless steel 1.4401/1.4408