
K-BKR KL SERIE 375

Ball valves, 375 series



max. 70 bar (depending on temperature and nominal size)		
G 1/4 to G 1: 20 °C: 70 bar, 60 °C: 65 bar, 100 °C: 45 bar, 150 °C: 7 bar, 180 °C: 4 bar, 200 °C: 0 bar G 1 1/4 to G 1 1/2: 20 °C: 70 bar, 60 °C: 55 bar, 100 °C: 35 bar, 150 °C: 7 bar, 180 °C: 4 bar, 200 °C: 0 bar G 2: 20 °C: 60 bar, 60 °C: 40 bar, 10		
200 °C at 0 bar		
15 % RPTFE (glass fibre reinforced PTFE)		
Stainless steel 1.4301		





Указание

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211) Други данни при запитване.

Указания за поръчка

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Допълнителна информация

G thread acc. DIN EN ISO 228-1

DN	Резба	A (mm)	B (mm)	L (mm)	Материал
5	G 1/4	69,0	34,0	39,0	Stainless steel 1.4401/1.4408
7	G 3/8	83,0	38,0	44,0	Stainless steel 1.4401/1.4408
10	G 1/2	96,0	41,0	59,0	Stainless steel 1.4401/1.4408
13	G 3/4	96,0	45,0	60,0	Stainless steel 1.4401/1.4408
16	G 1	116,0	52,0	72,0	Stainless steel 1.4401/1.4408
20	G 1 1/4	116,0	57,0	77,0	Stainless steel 1.4401/1.4408
25	G 1 1/2	158,0	62,0	84,0	Stainless steel 1.4401/1.4408
32	G 2	158,0	68,0	100,0	Stainless steel 1.4401/1.4408
	5 7 10 13 16 20 25	5 G 1/4 7 G 3/8 10 G 1/2 13 G 3/4 16 G 1 20 G 1 1/4 25 G 1 1/2	(mm) 5 G 1/4 69,0 7 G 3/8 83,0 10 G 1/2 96,0 13 G 3/4 96,0 16 G 1 116,0 20 G 1 1/4 116,0 25 G 1 1/2 158,0	(mm) (mm) 5 G 1/4 69,0 34,0 7 G 3/8 83,0 38,0 10 G 1/2 96,0 41,0 13 G 3/4 96,0 45,0 16 G 1 116,0 52,0 20 G 1 1/4 116,0 57,0 25 G 1 1/2 158,0 62,0	(mm) (mm) (mm) 5 G 1/4 69,0 34,0 39,0 7 G 3/8 83,0 38,0 44,0 10 G 1/2 96,0 41,0 59,0 13 G 3/4 96,0 45,0 60,0 16 G 1 116,0 52,0 72,0 20 G 1 1/4 116,0 57,0 77,0 25 G 1 1/2 158,0 62,0 84,0