

K-W90 VERSCHR PFA

Union elbows - Perfluoroalkoxy alkane (PFA)

Свойства

| | |
|---------------------|--|
| Работно налягане | Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 1 bar (at 170 °C) |
| работна температура | Max. 200 °C |
| Материал | Perfluoroalkoxy alkane (PFA) |



Указание

Други данни при запитване.

Описание

Perfluoroalkoxy alkane (PFA): A fluoroplastic (PTFE) with the same chemical resistance as PTFE but much stronger and suitable for temperatures up to 200°C.

Артикул

| Обозначение | Резба | за маркуч | L1 (mm) | L2 (mm) |
|----------------|-------|--------------|------------|------------|
| K- 07 40 41 80 | G 1/8 | 4 mm / 6 mm | 25,0 | 20,0 |
| K- 07 40 41 82 | G 1/8 | 6 mm / 8 mm | 30,0 | 23,0 |
| K- 07 40 41 84 | G 1/8 | 8 mm / 10 mm | 36,0 | 25,0 |
| K- 07 40 41 87 | G 1/4 | 4 mm / 6 mm | 26,0 | 25,0 |
| K- 07 40 41 89 | G 1/4 | 6 mm / 8 mm | 30,0 | 27,0 |
| K- 07 40 41 91 | G 1/4 | 8 mm / 10 mm | 36,0 | 32,0 |
| K- 07 40 41 94 | G 3/8 | 4 mm / 6 mm | 29,0 | 30,0 |
| K- 07 40 41 96 | G 3/8 | 6 mm / 8 mm | 33,0 | 27,0 |
| K- 07 40 41 98 | G 3/8 | 8 mm / 10 mm | 36,0 | 29,0 |
| K- 07 40 42 01 | G 1/2 | 4 mm / 6 mm | 32,0 | 29,0 |
| K- 07 40 42 03 | G 1/2 | 6 mm / 8 mm | 36,0 | 29,0 |
| K- 07 40 42 05 | G 1/2 | 8 mm / 10 mm | 39,0 | 31,0 |