

# K-SPIR SCHL KUPPL SET SVKM

Spiral hose and coupling kits, with quick disconnect couplings DN 7.6

**HANSA FLEX**

## Свойства

|                        |                  |
|------------------------|------------------|
| Работно налягане       | 10 bar           |
| температура на средата | -20 °C to +60 °C |



## Указание

Други данни при запитване.

## Описание

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

## Артикул

| Обозначение    | размер на маркуч | Ø спирала (mm) | работна дължина (m) |
|----------------|------------------|----------------|---------------------|
| K- 07 10 07 59 | 10 mm x 6,5 mm   | 52             | 4,0                 |
| K- 07 10 07 60 | 10 mm x 6,5 mm   | 52             | 6,0                 |
| K- 07 10 07 61 | 10 mm x 6,5 mm   | 52             | 8,0                 |
| K- 07 10 07 62 | 12 mm x 8 mm     | 65             | 4,0                 |
| K- 07 10 07 63 | 12 mm x 8 mm     | 65             | 6,0                 |
| K- 07 10 07 64 | 12 mm x 8 mm     | 65             | 8,0                 |