

K-VT 2 KUPPL 7,2 STECKNIP MS

Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8

HANSA FLEX

Свойства

Работно налягане	0 - 35 bar
температура на средата	-20 °C to +100 °C
корпус	Brass
предпазител и уплътнение	Industrial glue, mid hardened



Указание

Couplings and distributors are also available separately
Други данни при запитване.

Описание

1, 2 or 3-way distributor pieces made of brass, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Допълнителна информация

Couplings and distributors are also available separately

Артикул

Обозначение	Съединение	Куплунг	състои се от разпределител
K- 07 40 40 48	Plugs DN 7.2 to 7.8 / G 3/8	K-07350025	K-07404016
K- 07 40 44 27	Plugs DN 7.2 to 7.8 / G 1/2	K-07350026	K-07404017

е принадлежност към следните продукти

K-VSEH 3-KRAFT	Receptacle combinations »3-Kraft«
K-VSEH AIRKRAFT	Receptacle combinations »airkraft«