

K-NIPP KUPPL NW7 SCHL MS NI K

Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring

HANSA FLEX

Свойства

Работно налягане	0 - 35 bar, maximum static working pressure (non-pulsating)
температура на средата	-20 °C to +100 °C
Материал	месинг никелиран



Указание

Други данни при запитване.

Артикул

Обозначение	дефиниция	SW (mm)
K- 07 35 12 70	Plug for Hose 6x4with swivel nut and kink protector spring	-
K- 07 35 12 71	Plug for hose 8x6 with swivel nut and kink protector spring	-
K- 07 35 01 90	Plug for hose 10x8 with swivel nut and kink protector spring	17
K- 07 35 01 91	Plug for hose 12x9 with swivel nut and kink protector spring	17

е допълнителен елемент към следните продукти

K-SVKM NW 7,8 AG H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, male
K-SVKM NW 7,8 IG H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, female
K-SVKM NW 7,8 SCHL TUE H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem
K-LKM S NW7,8 AG	Safety couplings DN 7.8, male
K-LKM S NW7,8 IG	Safety couplings DN 7.8, female
K-LKM S NW7,8 SCHL TUE	Safety couplings DN 7.8, with hose stem