K-EINGANGSPL VENTILINSEL HDM

Input plates for HDM valve terminal

Свойства

Течности	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
работно налягане	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
налягане на управление	3 - 7 bar
Температурен диапазон	-10 °C to +60 °C
протичане	200 Nl/min (Ø 4), 500 Nl/min (Ø 6), 800 Nl/min (Ø 8)
брой на задействанията	Max. 16 (e.g. 16 spring return valves)
ръчно помощно задействане	Latching (bistable), Monostable (non-latching) version also available on request
консумирана енергия	0.6 W per pilot
вид защита	IP 65



Указание

Други данни при запитване.

Описание

These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks tot he wide range of functions and various input and intermediate plates.Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Допълнителна информация

Important: The scope of supply does not include a connector. Please order separately.

Артикул

Обозначение	функция	Съединение
K- 07 15 22 49	Standard, internal pilots	Multi-pole
K- 07 15 22 48	External pilots, dual supply	Multi-pole
K- 07 15 22 54	Standard, internal pilots	With integrated Profibus DP
K- 07 15 22 53	External pilots	With integrated Profibus DP

Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.