

# K-KALIBRIER-TEST UND SERVICE

Calibration, testing and service unit

**HANSA FLEX**

## Свойства

|                                      |                                       |
|--------------------------------------|---------------------------------------|
| Изпълнение                           | Calibration, testing and service unit |
| точност                              | 0,25% FS                              |
| температура на измерваното вещество  | -20 °C to +80 °C                      |
| околна температура                   | -10 °C to +50 °C                      |
| части в допир с измерваното вещество | CrNi-steel with NBR seal              |
| корпус                               | Die-cast zinc                         |



## Указание

Други данни при запитване.

## Описание

Service case for quick and precise pressure gauge calibration. Suitable for service and maintenance providers of all kinds as well as instrumentation control workshops and quality assurance. Simple operation using four buttons. The high sampling rate (100 measurements / second) guarantees an accurate analysis at the measuring point. Comprised of a CPG500 digital gauge and a CPP40 pneumatic hand test pump with a connecting cable for pressure generation. Operating manual, calibration certificate 3.1, two AA batteries and a protective rubber cap for the housing are enclosed. Includes a plastic emergency case with foam padding.

## Допълнителна информация

Further measuring ranges on request

## Артикул

| Обозначение    | Диапазон на измерване | Съединение |
|----------------|-----------------------|------------|
| K- 07 20 12 70 | -0.95 / +40 bar       | G 1/4      |