K-TR PVC SET

PVC air hose kits

Свойства

работна температура	-15 °C до +60 °C



Указание

Други данни при запитване.

Описание

Flexible, pressure-resistant and non-abrasive standard hose, also resistant to ageing. Assembled with brass stem and brass quick disconnect coupling DN 7.2.

Артикул

Обозначение	Ø маркуч отвътре (mm)	Ø маркуч отвън (mm)	Max. working pressure resistance at 23°C (bar)	дължина маркуч (m)
K- 07 10 12 13	6,0	12,0	15	5
K- 07 10 12 09	6,0	12,0	15	10
K- 07 10 12 10	6,0	12,0	15	15
K- 07 10 12 11	6,0	12,0	15	20
K- 07 10 12 12	6,0	12,0	15	25
K- 07 10 12 18	9,0	15,0	15	5
K- 07 10 12 14	9,0	15,0	15	10
K- 07 10 12 15	9,0	15,0	15	15
K- 07 10 12 16	9,0	15,0	15	20
K- 07 10 12 17	9,0	15,0	15	25
K- 07 10 12 08	13,0	20,0	15	5
K- 07 10 12 07	13,0	20,0	15	10

Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.