

# K-LKM S NW7,4 IG

## Safety couplings DN 7.4, female

HANSA FLEX

### Свойства

Работно налягане	Max. 12 bar, maximum static working pressure (non-pulsating)
работно налягане сменяеми съединителни втулки и нипели	0 to 35 bar
протичане въздух	1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)
температура на средата	-20 °C to +60 °C
корпус, корпус на клапан	Nickel-plated brass
клапан	Brass
деблокираща втулка	Plastic
пружина, пружинен спирачен пръстен, щифтове, сачми	Stainless steel
уплътняващ материал	NBR



### Указание

Други данни при запитване.

### Описание

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

### Артикул

Обозначение	Съединение	Дължина (mm)	SW (mm)
K-07 35 03 01	G 1/4 female	57,2	22
K-07 35 03 02	G 3/8 female	60,2	24
K-07 35 03 03	G 1/2 female	60,2	24

### Допълнителни елементи

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 2	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,