

K-DMUF ALLGEMEIN

Pressure transmitters for universal industrial applications, nonlinearity 0.25%

HANSA FLEX

Свойства

тип	S-20
напрежение	DC 8 ... 36 V
електрическо съединение	With right-angle connector acc. to DIN EN 175301-803 A
вид защита	IP 65 acc. to EN 60529
изходящ сигнал	4 to 20 mA, 2-wire
нелинейност	up to 0.25% of span
температура на средата	-30 °C to +100 °C
околна температура	-40 °C to +70 °C
части в допир с измерваното вещество	CrNi steel 1.4571
корпус	CrNi steel 1.4571



Описание

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development. Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry. Compatible with all internationally established process connections.

Допълнителна информация

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Артикул

Обозначение	Диапазон на измерване	Резба
K- 07 20 12 55	-1 / 0.0 bar	G 1/2
K- 07 20 12 56	0 - 0.4 bar	G 1/2
K- 07 20 12 57	0 - 1.0 bar	G 1/2
K- 07 20 12 64	0 - 4.0 bar	G 1/2
K- 07 20 12 67	0 - 6.0 bar	G 1/2
K- 07 20 12 58	0 - 10.0 bar	G 1/2
K- 07 20 12 60	0 - 16.0 bar	G 1/2
K- 07 20 12 62	0 - 25.0 bar	G 1/2
K- 07 20 12 65	0 - 40.0 bar	G 1/2
K- 07 20 12 68	0 - 60.0 bar	G 1/2
K- 07 20 12 59	0 - 100.0 bar	G 1/2
K- 07 20 12 61	0 - 160.0 bar	G 1/2
K- 07 20 12 63	0 - 250.0 bar	G 1/2
K- 07 20 12 66	0 - 400.0 bar	G 1/2
K- 07 20 12 69	0 - 600.0 bar	G 1/2