K-TR POLYURETHAN

Polyurethane hose (PUR)



Свойства			
работно налягане	Max. 10 bar (at +20 °C)		
твърдост	52 Shore D±3		
калибриране	External		
околна температура	-35 °C to +80 °C		
Материал	полиуретан		



Указание

Други данни при запитване.

Описание

This externally calibrated plastic hose made of high-quality polyester PUR is extremely flexible with optimal mechanical characteristics and very high pressure resistance across a wide temperature range. It is permanently flexible, boasts very good resilience and can be laid with a narrow bending radius. Its other advantages include good abrasion resistance, very good low-temperature flexibility and very high elongation at break. The hose is also suitable for vacuum applications. It is resistant to many different oils and lubricants (a special resistance test is recommended in specific cases owing to the additives that are blended in by the manufacturers), aliphatic hydrocarbons and gases such as oxygen, ozone, helium, etc.

Артикул							
Обозначение	Ø маркуч отвътре ^(mm)	Ø маркуч отвън ^(mm)	радиус на огъване в зависимост от протичането (mm)	Цвят	Дължина на ролката ^(m)		
K- 07 10 05 47	2,6	4,0	17	Natural	25		
K- 07 10 05 49	3,1	5,0	15	Natural	100		
K- 07 10 05 48	3,1	5,0	15	СИН	100		
K- 07 10 05 51	9,0	12,0	67	Natural	100		
K- 07 10 05 52	9,0	12,0	67	черен	100		
K- 07 10 05 54	9,8	14,0	72	Natural	50		
K- 07 10 05 53	9,8	14,0	72	СИН	50		
K- 07 10 05 55	9,8	14,0	72	черен	50		
K- 07 10 05 56	11,0	16,0	88	Natural	50		
K- 07 10 05 57	11,0	16,0	88	черен	50		