

# K-WV 3/2 LB NAMUR GETAUSCHT

3/2-way spool valves with NAMUR style interface, NC, ports 1 and 3 or 2 and 3 swapped

**HANSA FLEX**

## Свойства

|                                  |   |
|----------------------------------|---|
| Течности                         | Air, neutral gases, filtered                                  |
| работно налягане                 | 1.5 to 10 bar   |
| работна температура              | -20 °C to +70 °C  |
| електрическо съединение          | Plug connector PG 9   |
| Съдържа се в обема на доставката | Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws |
| консумирана енергия              | 3 W=/5 VA~  |
| корпус                           | Aluminium, anodised   |
| шибър                            | Stainless steel   |
| уплътняващ материал              | NBR   |



## Указание

Други данни при запитване.

## Описание

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Two or three-piece service units with excellent flow rates in modern design. <br>Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.<br>

## Артикул

| Обозначение    | Напрежение   | Съединение | DN | протичане (L/min) |
|----------------|--------------|------------|----|-------------------|
| K- 07 15 00 05 | 230 V, 50 Hz | G 1/4      | 7  | 1250              |
| K- 07 15 00 06 | 24 V DC      | G 1/4      | 7  | 1250              |