


# K-BKR GELB STAHLHEBEL IG IG

Ball valves with yellow steel lever, lightweight type, female/female thread

**HANSA FLEX**

## Свойства

|                        |  |
|------------------------|--|
| Диапазон на използване | Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture |
| Работно налягане       | Max. 40 bar  |
| работна температура    | -15 °C to +90 °C   |
| резба описание         | G thread acc. DIN EN ISO 228-1   |
| корпус                 | Nickel-plated brass  |
| лост                   | Steel, with plastic coating  |
| сачма                  | Chrome-plated brass  |
| сферично уплътнение    | PTFE   |
| уплътнение на шпиндел  | HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE) additional PTFE-gasket     |



## Указание

Други данни при запитване.

## Артикул

| Обозначение    | DN | Резба   | A<br>(mm) | B<br>(mm) | L<br>(mm) |
|----------------|----|---------|-----------|-----------|-----------|
| K- 07 30 00 81 | 8  | G 1/4   | 85,0      | 42,0      | 39,0      |
| K- 07 30 00 85 | 10 | G 3/8   | 85,0      | 42,0      | 43,0      |
| K- 07 30 00 89 | 15 | G 1/2   | 85,0      | 46,0      | 50,0      |
| K- 07 30 00 93 | 20 | G 3/4   | 105,0     | 53,0      | 58,0      |
| K- 07 30 00 97 | 25 | G 1     | 105,0     | 57,0      | 69,0      |
| K- 07 30 01 01 | 32 | G 1 1/4 | 130,0     | 70,0      | 81,0      |
| K- 07 30 01 05 | 40 | G 1 1/2 | 130,0     | 76,0      | 93,0      |
| K- 07 30 01 09 | 50 | G 2     | 165,0     | 92,0      | 110,0     |