


K-BKR LANG IG IG

Ball valves, long-threaded type, female/female thread

HANSA**FLEX**

Свойства

Диапазон на използване	Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture
Работно налягане	Max. 40 bar
работна температура	-15 °C to +90 °C
ръзба описание	Thread acc. to ISO 7-1
корпус	Nickel-plated brass
лост	Aluminium, painted black
сачма	Chrome-plated brass
сферично уплътнение	PTFE
уплътнение на шпиндел	NBR / EPDM



Указание

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Други данни при запитване.

Указания за поръчка

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Допълнителна информация

The pressure values refer to a maximum operating temperature of 40 °C. Lower maximum pressure apply at higher temperatures. See data sheet.

Артикул

Обозначение	DN	Резба	A (mm)	B (mm)	L (mm)
K-07 30 21 45	8	Rp/Rp 1/4	85,0	42,0	49,0
K-07 30 21 46	10	Rp/Rp 3/8	85,0	42,0	50,0
K-07 30 21 47	15	Rp/Rp 1/2	85,0	46,0	61,0
K-07 30 21 48	20	Rp/Rp 3/4	105,0	53,0	70,0
K-07 30 21 49	25	Rp/Rp 1	105,0	57,0	84,0
K-07 30 21 50	32	Rp/Rp 1 1/4	130,0	70,0	97,0
K-07 30 21 51	40	Rp/Rp 1 1/2	130,0	76,0	108,0
K-07 30 21 52	50	Rp/Rp 2	165,0	92,0	130,0