

K-SVKM NW 7,8 AG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, male

HANSA FLEX

Свойства

Работно налягане	0 - 35 bar
протичане въздух	2.100 l/min (at $\Delta p = 0.5$ bar)
температура на средата	-20 °C to +40 °C
резбови детайл	Nickel-plated brass
корпус на клапан	Steel, QPQ treated
деблокираща втулка	Extremely robust, ergonomic plastic
клапан, гнездо	Brass
Течности	Only for clean compressed air
уплътнения	NBR
пружина, пружинен спирачен пръстен, сачми	stain less steel



Указание

Други данни при запитване.

Описание

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Артикул

Обозначение	Съединение	Дължина (mm)	SW (mm)
K- 07 35 08 47	G 1/4 male	65,0	19
K- 07 35 08 48	G 3/8 male	65,0	19
K- 07 35 08 49	G 1/2 male	59,0	22

Допълнителни елементи

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass